

SPEKIFIKASI	FAW
<i>Model</i>	DB130MT
<i>Drive Wheel</i>	4x2
<i>Engine</i>	
Model	Yuchai YC4D130-33
Type	diesel engine, 4 cylinder inline, intercooling, turbo charge
Power (HP/rpm)	130/2800
Displacement (L)	4.214
Torque (Nm/(r/min))	380/1400-1700
<i>Dimension</i>	
Length (mm)	6816
Width (mm)	1995
Height (mm)	3330
Wheel Base (mm)	3500
Front Overhang (mm)	1346
Rear Overhang (mm)	1972
<i>Mass</i>	
Curb Weight (kg)	2880
GVW (kg)	10000
<i>Performance</i>	
Turning Radius (m)	6.55
Max. Speed (km/h)	105
Gradeability (%)	30
Fuel Tank Capacity (L)	80
<i>Axle</i>	
Reduction	Single
Inter Axle Differential Lock	No
Inter Axle Wheel Lock	No
Ratio	4.875
<i>Transmission</i>	
Model	WLY5T46
Forward Shift Ratio	7.312; 4.311; 2.447; 1.535; 1.00
Reverse Shift Ratio	6.972
<i>Clutch</i>	
Type	Dry type, single plate, diaphragm spring clutch, hydraulic controlled, and air auxiliary power supply
Diameter (mm)	325
<i>Electronical System</i>	
Type	Single Line, Negative Grounded
Battery (V/Ah)	2x12/90
<i>Wheel</i>	

Rim	6.5H-16
Tire	8.25R16
<i>Break System</i>	
Drive Brake	Double Circuit Full Air Brake
Parking Brake	Central Brake Type
Auxiliary Brake	Exhaust and Engine Brake